



## Key Features

- Direct replacement for Breezair and Wine Mate
- Dynamic airflow
- 30°F temperature differential
- Flexible mounting bracket
- Advanced digital controller
- Built-in air sensor

## Specifications

| Model  | CX2200/CX2200-RPC   | CX3300/CX3300-RPC           | CX4400/CX4400-RPC | CX8800/CX8800-RPC        |
|--|---|-----------------------------|-------------------|--------------------------|
| Cellar Size (cu. ft.)                          | 300*  | 650*                        | 1000*             | 2000*                    |
| BTU/h (w/85°F air entering the condenser coil) | 1453  | 2049                        | 2962              | 4754                     |
| CFM  | 118   | 126                         | 216               | 374                      |
| Dimensions                                     | 16.38"L x 14.25"W x 13.25"H   | 21.63"L x 14.25"W x 19.75"H |                   | 22.25"L x 16.25"W x 22"H |
| Refrigerant                                    | R-134a  | R-134a                      | R-134a            | R-134a                   |
| HP   | 0.57  | 0.8                         | 1.16              | 1.86                     |
| Voltage Rating                                 | 115V (20 amp dedicated circuit required)  |                             |                   |                          |
| Weight (lb.)                                   | 65  | 66                          | 67                | 74                       |
| Amps   | 4.5 (running amps)  | 4.9 (running amps)          | 9 (running amps)  | 10 (running amps)        |
| dBA (Evaporator/Condenser)                     | 63 / 63   | 63 / 64                     | 63 / 64           | 68 / 68                  |
| Drain Line                                     | 3/8" Condensate (rear location only)  |                             |                   |                          |
| Installation                                   | Through-the-wall, partially ducted  |                             |                   |                          |
| Thermostat                                     | Advanced digital display  |                             |                   |                          |
| Temp. Delta                                    | Can maintain a 55°F cellar temperature with up to 85°F condenser air intake temperature |                             |                   |                          |
| Warranty                                       | 2-year parts and labor / 5-year compressor  |                             |                   |                          |

RPC — Rear Power Cord

\*Approximated in an environment that is fully insulated and sealed with a proper vapor barrier. Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.