



Key Features

- Two-speed fan switch
- Up to 45% more capacity
- UV-C Light System add-on
- Customizable front panel
- 30°F temperature differential
- Can be mounted above a door
- Condensate management system
- Smart controlled ECM condenser fan
- Liquid temperature measuring bottle probe
- Strategic relocation of internal components

Features

Say hello to the first unit in our new luxury series (LS). The Slimline LS can cool at two capacities at the flip of a switch. We have added centrifugal blowers, which are significantly quieter and can also be set at a medium or low speed, larger coils for greater system capacity, and an improved condensate management system. The condenser (exhaust) blower has been upgraded to an ECM fan, capable of automatically adjusting speed to provide the ideal airflow needed to dissipate excess heat. The controller has been moved to the condenser side of the unit for easy access. We offer a UV-C Lighting System upgrade to protect your unit from VOCs and an interchangeable faceplate which allows you to customize the look of your cooling system.

Specifications

Fan Speed	Low	Medium
Cellar Size	300 cu. ft.*	650 cu. ft.*
BTU/h (60°F condenser air intake temperature)	2601/1961 (total/sensible)	3032/2413 (total/sensible)
BTU/h (75°F condenser air intake temperature)	2635/1951 (total/sensible)	2904/2309 (total/sensible)
BTU/h (85°F condenser air intake temperature)	2396/1870 (total/sensible)	2612/2158 (total/sensible)
BTU/h (95°F condenser air intake temperature)	2205/1704 (total/sensible)	2392/2008 (total/sensible)
CFM	81	111
Dimensions	21.5"L x 22.16"W x 10.33"H	
Refrigerant	R-134a	
HP	1/5	
Voltage Rating	115V (20 amp dedicated circuit required); 230V (subject to availability)	
Weight (lbs)	81 lbs. without packaging, 90 lbs. with packaging	
Amps	4.3 (running amps)	
Drain Line	1/2" ID clear plastic tubing (not provided)	
Installation	Through the wall, ideally above a doorway	
Thermostat	Advanced digital display, liquid-temperature-measuring bottle probe (retractable cable)	
Temp. Delta	Can maintain a 55°F cellar temperature with up to 85°F condenser air intake temperature	
Warranty	2-year limited warranty & up to an additional (6) month grace period for install / 5-year limited warranty (compressor)	

*Suggested cubic footage rating assumes cellar is properly sealed and insulated with a minimum R19 insulation value. Materials such as glass, stone, concrete, etc., will negatively affect the insulation value. Each wine cellar is unique, and heat load calculations should always be performed prior to selecting a cooling unit. WhisperKOOL reserves the right to make changes to this document without prior notice at its sole discretion.

